









LAMPARAS PL & DOWNLIGHT

| Foto | Modelo | Potencia Watts | Piezas (Led) | Marca del LED | Angulo de visión | Lumens | Temperatura de color | Tensión | Casquillo / Conector | Vida útil aprox. hrs. |
|---|--------------------|----------------|--------------|------------------|------------------|---------------|----------------------|------------------|----------------------|-----------------------|
|  | SEPL-G24D3-11S50-1 | 11 | 50 | EPISTAR SMD 5050 | 120° | 700 | 2.800 K | 110 / 230 V. AC. | G24D3 | 30.000 - 50.000 Hrs. |
| | SEPL-G24D3-11S50-2 | 11 | 50 | EPISTAR SMD 5050 | 120° | 800 | 6.500 K | 110 / 230 V. AC. | G24D3 | 30.000 - 50.000 Hrs. |
|  | SEPL-G24D3-13S60-1 | 13 | 60 | EPISTAR SMD 5050 | 120° | 850 | 2.800 K | 110 / 230 V. AC. | G24D3 | 30.000 - 50.000 Hrs. |
| | SEPL-G24D3-13S60-2 | 13 | 60 | EPISTAR SMD 5050 | 120° | 950 | 6.500 K | 110 / 230 V. AC. | G24D3 | 30.000 - 50.000 Hrs. |
|  | | | | | | | | | | |
| | SEPL-G24D3-14S64-2 | 14 | 64 | EPISTAR SMD 5050 | 120° | 1050 | 6.500 K | 110 / 230 V. AC. | G24D3 | 30.000 - 50.000 Hrs. |
|  | SEPL-E27-11S50-1 | 11 | 50 | EPISTAR SMD 5050 | 120° | 700 | 2.800 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
| | SEPL-E27-11S50-2 | 11 | 50 | EPISTAR SMD 5050 | 120° | 800 | 6.500 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
|  | SEPL-E27-13S60-1 | 13 | 60 | EPISTAR SMD 5050 | 120° | 850 | 2.800 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
| | SEPL-E27-13S60-2 | 13 | 60 | EPISTAR SMD 5050 | 120° | 950 | 6.500 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
|  | SEPL-E27-14S64-1 | 14 | 64 | EPISTAR SMD 5050 | 120° | 1050 | 2.800 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
| | SEPL-E27-14S64-2 | 14 | 64 | EPISTAR SMD 5050 | 120° | 1050 | 6.500 K | 110 / 230 V. AC. | E27 | 30.000 - 50.000 Hrs. |
|  | | | | | | | | | | |
| | VEDW-R-12S12-2 | 12 | 12 | - | - | 820 / 950 | 6.500 K | 100 / 240 V. | - | 30.000 - 50.000 Hrs. |
|  | | | | | | | | | | |
| | VEDW-R-15D15-2 | 15 | 15 | - | - | 1.050 / 1.200 | 6.500 K | 100 / 240 V. | - | 30.000 - 50.000 Hrs. |